

### PRODUCT OF GROUP VIEW:



### FEATURES:

- \* 1.5K Series 6.5" High Performance Car Subwoofer
- \* 450W RMS Handling Power, 900W Max.Power
- \* Normal Dual 4 Ohm or Dual 2 Ohm Impedance input
- \* Die-cast Aluminum Frame
- \* Non-pressed Paper cone with carbon fiber reinforced
- \* Stitching Foam Surround
- \* High Efficiency Double Ferrite Magnet with Rubber boot
- \* High-temp 4Layers Round Copper Wound Coil

### SPECIFICATIONS:

Product Type	Subwoofer Chassis
Magnet Dimension	140*40mm
Magnet Weight	2x40Oz
Magnet Efficiency	Y35
Spider Material	Nomex Spider Pack
Lead Wire Diemnsion	63GA
Lead Wire Materials	Braid Flat Tinsel
Voice Coil Wire Material	Round Copper
Voice Coil Former Magerial	Black Aluminum
Voice Coil Diameter	50.8mm/2"
Voice Coil Winding Height	35mm/1.38"
Top plate height	12mm / 0.47"
Linear Exursion (one-way)	15mm / 0.59"
Woofer Displacement	0.05ft <sup>3</sup> / 1.42L

### T/S PARAMETERS:

Model No.	TZ61.5KD2G2	TZ61.5KD4G2
Fs	62.6 Hz	53.6 Hz
Re	2+2 Ohm	4+4 Ohm
Qms	4.72	4.85
Qes	0.54	0.65
Qts	0.49	0.55
Mms	110.59	90.78
Bl	17.93	20.35
SPL (1M/1W)	80.1 dB	79.9 dB
Vas	1.46 L	1.6 L
X-max (one way)	15mm	15mm
N.W.	13.25Lbs	13.25Lbs

### SUBWOOFER DIMENSION:

Model No.	TZ61.5KDG2
A	7.16"
B	6.38"
C	5.9"
D	5.98"
E	5.12"

