

### PRODUCT OF GROUP VIEW:



### FEATURES:

- \* 1.5K Series 8" High Performance Car Subwoofer
- \* 750W RMS Handling Power, 1500W Max. Power
- \* Normal Dual 4 Ohm or Dual 2 Ohm Impedance input
- \* Die-cast Aluminum Frame
- \* Non-pressed Paper cone with carbon fiber reinforced
- \* Stitching Foam Surround
- \* High Efficiency Double Ferrite Magnet with Rubber boot
- \* High-temp 4Layers Round Copper Wound Coil

### SPECIFICATIONS:

Product Type	Subwoofer Chassis
Magnet Dimension	170*50mm
Magnet Weight	2x750z
Magnet Efficiency	Y35
Spider Material	Nomex Spider Pack
Lead Wire Dimension	84GA
Lead Wire Materials	Braid Flat Tinsel
Voice Coil Wire Material	Round Copper
Voice Coil Former Material	Black Aluminum
Voice Coil Diameter	63.5mm/2.5"
Voice Coil Winding Height	45mm/1.77"
Top plate height	20mm / 0.79"
Linear Excursion (one-way)	19mm / 0.75"
Woofer Displacement	0.06ft <sup>3</sup> / 1.69L

### T/S PARAMETERS:

Model No.	TZ81.5KD2G2	TZ81.5KD4G2
Fs	38 Hz	41.6 Hz
Re	2+2 Ohm	4+4 Ohm
Qms	5.24	5.03
Qes	0.40	0.51
Qts	0.37	0.47
Mms	139.5	132.8
Bl	18.4	23.3
SPL (1M/1W)	81.9 dB	81.4 dB
Vas	7.2 L	6.3 L
X-max (one way)	19mm	19mm
N.W.	25.35Lbs	25.35Lbs

### SUBWOOFER DIMENSION:

Model No.	TZ81.5KDG2
A	8.66"
B	7.87"
C	7.17"
D	7.68"
E	6.42"

